

MATERIALS FOR 3D PRINTING **NYLON** 



# PA12 - PA2200

# White nylon



PA12 is the most widely used material for 3D printing with Selective Laser Sintering, as you can print fully functional parts with good mechanical and thermal properties. It is possible provide nylon with a 3S surface treatment. This significantly reduces moisture absorption and a smoother surface is achieved. 3S surface treated nylon is approved as food contact material (FCM)

We print with Selective Laser Sintering (SLS). The technology prints in powder and uses a laser to sinter the powder layers together. 3D printing with SLS offers a great deal of design freedom, as the parts do not need support material.

The technology can produce parts that comply with ISO 2768-m 1; however, the tolerances depend significantly on the geometry of the part. At the Danish Technological Institute, our 3D printing production is also ISO 9001 certified.

MATERIAL PROPERTIES	
TENSILE STRENGTH [Rm]	48 MPa
YIELD STRENGTH [Rp0,2]	44 MPa
ELONGATION AT BREAK [A]	22 %
VICKERS HARDNESS [Shore D]	80,6
PART DENSITY	>96,0 %
MATERIAL MASS DENSITY	0,95 g/cm³

SURFACE TEXTURE	Raw	3S surface sealing
Average roughness [Ra]	10 ±3	1,2*

<sup>\*</sup>Depending on geometry

# Danish Technological Institute - Industrial 3D-printing

Email: 3dprint@dti.dk Phone: 7220 1701 www.dti.dk/3dprinting



# • V • V • S

# Visit our website to see our AM services

## Possible post-processing:

- Deburring
- Media blasting
- Colouring
- Lacquering
- 3S surface sealing

#### Build volume:

EOS: 340 x 340 x 600 mm

3D Systems - ProX 6100

• 3D: 381 x 330 x 460 mm

Select Laser Sintering

## Application:

Technology:

FOS - P396

Printer:

· Industrial use

#### **Customization:**

Contact us if you have specific requests for surface roughness and material properties.

### Design features:

- Minimum feature size 0.8 mm
- Minimum channel size Ø1.5 mm
- · Minimum wall thickness 0,7 mm
- Support not necessary
- Hole for emptying powder Ø5 mm

### Examples of use

- Hygienic nozzles and manifolds for food applications
- · Lightweight grippers for robotic handling
- · Machine components